

SCHEDULE #1
GENERAL INVENTORY
 TECHNICOIL CORPORATION – RIG NO. 2034
 Manufactured at Crown Industries
 Slant Capable CTU

DATE: **November 13, 2007**

GENERAL SPECIFICATIONS

DEPTH RATING	7601m.		1 ½" (38.1mm.)
	4900m.	With	2" (50.8mm.)
	2033m.		2 7/8" (73mm.)
	1486m.		3 ¼" (82.55mm.)
Slant Capable CTU	Injector Tilt	Max	57 degrees tilt
TOOL SPREADS	Double/Double cup tool	Max	11.7m
	Single/Single cup tool	Max	13m

EQUIPMENT

1.	CARRIAGE WINCH	Make	Pullmaster	Model	M25
	LUBRICATOR WINCH	Make	Pullmaster	Model	PL5
2.	RIG POWER & DISTRIBUTION	Description	Cummins ISX 565		
		Max. Continuous Power	565HP		
		Maximum Power	600HP		
3.	MAST	Make	Crown Industries	Length	18m.
		Maximum Hook Load	40,000# (17,793DaN)	w/	2 part line
		Bottom of stripper to ground	16m.	B.O.P Height	Wellhead dependent
4.	OVERALL DIMENSION	- Length	23.5m.		
	TRACTOR/TRAILER	- Width	3.3m.		
		- Height	4.55m.		
5.	GENERATOR	Make	Lima	Model	#3264-006-280
		Maximum Power	8kw 60Hz		
6.	INJECTOR	Make	Stewart and Stevenson	Model	M100
		Maximum Capacity	120,000# (53,380DaN)		
		Snubbing Capacity	40,000# (17,793)		
		Maximum Speed	35m/min.	Operating Speed	18m/min.
		Max. Tubing Size	3 ½" (88.9mm.)		

7.	BLOW-OUT PREVENTERS	Make	Vanoil Equipment	Pipe Rams	Blind Shears
		Size	5 1/8" (130.18mm.)	<u>Model</u>	P505DHBO
		Max. Pres.	5000psi (34,470kpa)		
		Tubing Size	2 7/8" (73.3mm.)	Max tubing size	3 1/2" (88.9mm.)
8.	STRIPPER PACKOFF	Make	Vanoil Equipment	<u>Model</u>	M4058800C
		Size	4 1/16"		
		Max. Pres.	5000psi (34,470kpa)		
		Max tubing size	3 1/2" (88.9m.)		
9.	LUBRICATORS	Make	Vanoil Equipment	<u>Model</u>	R-605GLA2
		Size	5 .050 (130.18mm.) Nominal Diameter		
		Max. Pres.	5000psi (34,470kpa)		
		Max tubing size	3 1/2" (88.9mm.)		
10.	CRANE SUPPORT TRUCK	Make	International	<u>Model</u>	HT-570
		Engine	DH330	<u>Horsepower</u>	190HP
		Crane	Fassi Knuckle Boom	<u>Lift Capacity</u>	5-ton
		Compressor	Atlas Copco	<u>Output</u>	250psi @ 400scf